

SAFETY DATA SHEET (SDS)

Section 1. Identification				
Product identifier	LABPOX MVB FAST-COLOR, Part A (Moisture Vapor Barrier Base Coat)			
Other means of identification MVB-A				
Recommended use and restrictions on use Vapor Moisture barrier epoxy coating				
Initial supplier identifier LabSurface. 101-1079 des Forges, Terrebonne, J6Y0J9, Qué (Canada) Tél. (450) 966-9000				
Emergency telephone number/restriction on use Canada – CANUTEC Number 24 hours 613-996-6666				
Section 2. Hazard Identification				

Classification of hazardous product (name of the category or subcategory of the hazard class)

Acute toxicity, oral, dermal and inhalation (Category 4)

Skin corrosion/irritation (Category 2)

Skin sensitization (Category 1)

Serious eye damage/eye irritation (Category 2A)

Carcinogenicity (Category 2)

Hazardous to the aquatic environment, long-term-hazard (Category 3)

Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)





Warning

H302 + H312 + H332 Harmful if swallowed, in contact with skin or if inhaled.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H412 Harmful to aquatic life with long lasting effects

Prevention

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P261 Avoid breathing dust/fume/gas/mist/vapors/spray. P264 Wash hands/nails/face/eyes thoroughly after handling. P270 Do not eat, drink or smoke when using this product P271 Use only outdoors or in a well ventilated area P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear gloves/protective clothing/gloves/eye protection/face protection.

Response

IF SWALLOWED: P301 + P312 Call a Poison Center/doctor if you feel unwell. P330 Rinse mouth.

IF ON SKIN: P302 + P352 Wash with plenty of water. P312 Call a POISON CENTER/doctor if you feel unwell. P362 + P364 Take off contaminated clothing and wash it before reuse. . P332 + P313 If skin irritation occurs: Get medical advice/attention

IF INHALED: P304 + P340 Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell.

IF IN EYES: P305 + P351 + P338 Rinse cautiously with water. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical attention.

IF exposed or concerned: P308 + P313 Get medical attention.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other	hazards	known	None

Section 3. Composition/Information on Ingredients				
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*		
Polymère en Bisphénol A / Epichlorohydrine	25085-99-8	> 60 %		
2,2'-[1,4-Butanediylbis(oxymethykene)bis[oxirane]	2425-79-8	< 10 - 30 %		
Aliphatic glycidyl ether	68609-97-2	1 – 10 %		
Colors may contain:				
Titanium dioxide	13463-63-7	< 25 %		
Amorphous silica	7631-86-9	< 2 %		
Aluminium hydroxide	21645-51-2	< 2 %		
Carbon black	1333-86-4	< 25 %		

*Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).

Section 4. First-Aid Measures

Inhalation IF INHALED: If overexposure remove person to fresh air and keep comfortable for breathing. If symptoms persist, seek medical attention.



Ingestion	IF SWALLOWED: Immediately call a doctor. Prevent aspiration of vomit. Never give anything by mouth to an unconscious			
8	person. Rinse mouth thoroughly with water.			
Skin contact	IF ON SKIN: Remove contaminated clothing,	wash immediately with soap and water (20 - 30 minutes). If skin irritation occurs:		
	Get medical attention. Wash contaminated co	lothing before reuse. Discard items which cannot be decontaminated, including		
	leather articles such as shoes, belts and watch	bands. If symptoms persist, seek medical attention.		
Eye contact		several minutes (20 - 30 minutes). Remove contact lenses, if present and easy to		
	do. Continue rinsing. If eye irritation persists:	Get medical attention.		
Most important	t important symptoms and effects (acute or delayed) Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation.			
	May cause an allergic skin reaction. Causes serious eye irritation. Suspected of			
causing cancer.				
Indication of in	ndication of immediate medical attention/special treatment In all cases, call a doctor. Do not forget this document.			
	Section 5.	Fire-Fighting Measures		
Specific hazard	s of the hazardous product (hazardous combu	stion products)		
Smoke, fume, ox	xides of carbon.			
Suitable and ur	nsuitable extinguishing media			
In case of fire: U	Jse Carbon dioxide (CO ₂), dry chemical, water ar	nd alcohol resistant foam.		

Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment as required

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Evacuate non-emergency personnel. Isolate the area and prevent access. Control source of the leak. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8). Prevent the spill spread into drains, sewers, water supplies, or soil. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Stop leak if you can do it without risk. Do not touch or walk through spilled material. Spill should be contained with inert material and disposed into suitable retaining area. Small volumes of liquid may be contained or absorbed into an appropriate absorbent. Keep away from all watercourses. Do not flush down storm or sanitary sewer. Take precautionary measures against static discharges. Dispose of in accordance with local, provincial and federal regulations.

Section 7. Handling and Storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands/nails /face/eyes thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear gloves/protective clothing/gloves/eye protection/face protection.

Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated area. Keep container closed when not in use. Do not handle or store near open flames, heat or other sources of ignition. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks. Storage temperature: 16 - 27 °C.

Section 8. Exposure Controls/Personal Protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits CAS 1333-86-4 – ACGIH – TLV-TWA 3 mg/m^3 PEL-TWA 3.5 mg/m^3 ; CAS 13463-63-7 ACGIH – TLV-TWA 10 mg/m^3 & PEL-TWA 10 mg/m^3 ; CAS 7631-86-9 PEL-TWA 80 mg/m^3 ; CAS 21645-51-2 ACGIH – TLV-TWA 1 mg/m^3

Appropriate engineering controls

Use product in well-ventilated areas. Do not spray the product. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Supply emergency safety/quick-drench shower, eyewash station and washing facilities available in work area and near handling area. Where such systems are not effective, wear suitable personal protection equipment which performs satisfactorily and meets recognized standards.

Individual protection measures/personal protective equipment

Gloves: Neoprene gloves or equivalent; Clothing: Shirts with long sleeves, long pants; Respiratory: Not required if working area is well ventilated. Use a NIOSH approved respirators if the exposure limits are unknown; Equipment: Safety glasses, chemical resistant. Special instructions for protection and hygiene: Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use. Educate and train employees in the safe use and handling of this product. Follow all label instructions.

Section 9. Physical and Chemical Properties					
Appeara	ance, physic	al state/colour	Liquid	Vapour pressure	Not available
Odour Faint odor		Vapour density	Not available		
Odour t	hreshold	Not available		Relative density	Not available



Solubility Not soluble		
Partition coefficient - n-octanol/water Not available		
Auto-ignition temperature Not available		
Decomposition temperature Not available		
Viscosity Not available		
VOC Not available		
Other None known		

Section 10. Stability and Reactivity

Reactivity

Stable under normal conditions.

Chemical stability

Yes, Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

Non under normal conditions of storage and use.

Conditions to avoid (static discharge, shock or vibration)

Excess heat.

Incompatible materials

Acids, bases, amines, oxidizing agents.

Hazardous decomposition products

Carbon oxides; by thermal decomposition: toxic vapors

Section 11. Toxicological Information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer.

Symptoms related to the physical, chemical and toxicological characteristics

No specific information available.

Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization - May cause allergic skin reaction. Skin disorders and Allergies. Respiratory Sensitization - No data available;

Germ Cell Mutagenicity – Animal genetic toxicity studies were negative; Carcinogenicity – Ingredients listed by IARC, ACGIH, NTP or OSHA; Reproductive Toxicity – In animal studies, did not interfere with reproduction;

Specific Target Organ Toxicity — Single Exposure – Evaluation of available data suggests that this material is not an STOT-SE toxicant; Specific Target Organ Toxicity — Repeated Exposure – Except for skin sensitization, repeated exposures to low molecular weight epoxy resins of this type are not anticipated to cause any significant adverse effects;

Aspiration Hazard – Based on physical properties, not likely to be an aspiration hazard; Health Hazards Not Otherwise Classified – No data available.

Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀)

CAS 25085-99-8 LD₅₀ Oral - Rat - > 15,000 mg/kg; LD₅₀ Dermal - Rabbit - 23,000 mg/kg; LC₅₀ Inhalation - has not been determined;

CAS 2425-79-8 LD_{50} Oral - Rat 1134 mg/kg; LD_{50} Dermal - Rabbit - 1130 mg/kg; LC_{50} Inhalation - Not available; ATE not available in this document.

Section 12. Ecological Information

Ecotoxicity (aquatic and terrestrial information)

Toxicity to fish CAS: 25085-99-8 LC₅₀: 1 – 10 mg/l (in the most sensitive species tested)/ LC₅₀ 2 mg/l (Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour; CAS: 2425-79-8 LC₅₀: 24 mg/l (Danjo rerio) 96 Hour; CAS: 68609-97-2 LC₅₀: 0,002 mg/l 96h;

Toxicity to Aquatic Invertebrates: CAS: 25085-99-8 EC₅₀: 1.8 mg/l (Water flea (Daphnia magna) 48h); 68609-97-2 EC₅₀: 10 mg/l (Daphnia magna);

Toxicity to Algae and Aquatic Plants: CAS: 25085-99-8 EC₅₀: 11 mg/l (Fresh water algae (Scenedesmus capricornutum) static test, 72h); CAS: 2425-79-8 EC₅₀: 75 mg/l (Daphnia magna) 48h;

Toxicity to Bacteria CAS: 25068-38-6 IC₅₀: >42.6 mg/l, (Respiration rates, 18h).

Persistence and degradability	CAS: 25085-99-8 12% 28 days, not easily biodegradable; CAS: 2425-79-8 Not readily biodegradable.
Bioaccumulative potential	CAS: 25085-99-8 Bio-concentration potential is moderate; CAS: 2425-79-8 Bioaccumulation is unlikely low
	Pow -1.33. CAS: 68609-97-2 log Koe : 7.25, FBC : 934,9

Mobility in soil CAS: 25085-99-8 Potential for mobility in soil is low; CAS: 2425-79-8 The product is water soluble and may spread in water systems. Highly mobile in soils. CAS: 68609-97-2: Koc: 12830

Other adverse effects Harmful to aquatic life with long lasting effects.

Section 13. Disposal Considerations

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Section 14. Transport Information

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations

Not regulated.

UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)



Not regulated.		
	oper shipping name; Class(es); Packing group (PG) of the IATA (air)	
Not regulated.		
Special precaut	ions (transport/conveyance) None	
Environmental	hazards (IMDG or other) None	
Bulk transport	(usually more than 450 L in capacity) None	
	Section 15. Regulatory Information	
Safety/health Ca	anadian regulations specifics This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).	
Environmental	Canadian regulations specifics Refer to Section 3 for ingredient(s) of the DSL	
Safety/health/er	nvironmental outside regulations specifics	
	SHA information: This product is regulated according to OSHA (29 CFR).	
	PA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.	
	CSA information: Refer to the ingredients listed in Section 3.	
	sition 65: For Color, White and Black WARNING: This product contains Titanium dioxide (CAS 13467-63-7) & Carbon black	
(CAS 1333-86-4)) known to the State of California to cause cancer or other reproductive harm.	
	Section 16. Other Information	
	st revision of the safety data sheet February 15, 2020 - version 01	
References	Safety Data Sheets from manufacturer/supplier & from Sigma-Aldrich.com & Echa.eurpea.eu	
Abbreviations		
ACGIH	American Conference of Governmental Industrial Hygienists	
ATE	Acute toxicity estimate	
CAS	Chemical Abstract Service	
DSL	Domestic Substance List	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods Code	
LC	Lethal concentration	
LD	Lethal Dosage	
NIOSH	National Institute for Occupational Safety and Health	
NTP	National Toxicology Program (U.S.A.) Occupational Safety and Health Administration (U.S.A.)	
OSHA PEL	· · · · · · · · · · · · · · · · · · ·	
STEL	Permissible Exposure Limit Short-term Exposure Limit	
TDG	Transport of dangerous goods in Canada	
TLV	Threshold Limit Value	
TSCA	Toxic Substances Control Act	
TWA	Time Weighted Average	
1 11 11	Time (Cognical Tropage	

WHMIS Workplace Hazardous Materials Information System

DISCLAMER: Labsurface expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages. Users are responsible to verify whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product.



SAFETY DATA SHEET (SDS)

Section 1. Identification				
Product identifier	Product identifier LABPOX MVB FAST, Part B (Moisture Vapor Barrier Base Coat)			
Other means of identification LPMVB-B				
Recommended use and restrictions on Vapor Moisture barrier epoxy coating				
use				
Initial supplier identifier LabSurface. 101-1079, rue des Forges, Terrebonne, QC, J6Y 0J9 (Canada) Tél. (450) 966-9000				
Emergency telephone number/restriction on use Canada – CANUTEC Number 24 hours 613-996-6666				
Section 2. Hazard Identification				

Section 2. Hazaru Identification

Classification of hazardous product (name of the category or subcategory of the hazard class)

Acute toxicity, oral and inhalation (Category 4)

Skin corrosion/irritation (Category 1B)

Skin sensitization (Category 1A)

Reproductive toxicity (Category 2)

Specific target organ toxicity, repeated exposure (Category 2)

Hazardous to the aquatic environment, long-term-hazard (Category 1)

Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)









Warning

H302 + H332 Harmful if swallowed, if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects.

Prevention

P201 Obtain special instruction before use. P202 Do not handle until all safety precautions have been read and understood. P260 + P261 Do not/avoid breath dust/fume/gas/mist/vapours/spry. P264 Wash hands/nails/face/eyes thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear gloves/protective clothing/gloves/eye protection/face protection.

Response

IF SWALOWED: P301 + P330 + P331 Rinse mouth. Do NOT induce vomiting.

IF ON SKIN: P302 + P352 Wash with plenty of water. P333 + P317 If skin irritation or rash occurs: Get medical help. P362 + P364 Take off contaminated clothing and wash it before reuse.

IF ON SKIN (OR HAIR): P303+P361+P353 Take off immediately all contaminated clothing. Rinse skin with water (or shower). P363 Wash contaminated clothing before reuse.

IF INHALED: P304 + P340 Remove person to fresh air and keep comfortable for breathing. P316 Get emergency medical help immediately.

IF IN EYES: P305 + P351 + P338 Rinse cautiously with water. Remove contact lenses, if present and easy to do. Continue rinsing.

IF EXPOSED OR CONCERNED: P308 + P316 Get emergency medical help immediately. ENVIRONMENT: P391 Collect spillage

Storage

P405 Stored locked up

Disposal

P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other hazards known None					
Section 3. Composition/Information on Ingredients					
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)*			
Aliphatic Amine	1477-55-0	15 - 40 %			
Trade secret		10 - 30 %			
4,4'-Diaminodicyclohexylmethane	1761-71-3	1 - 10 %			
Mixed Cycloaliphatic amines	135108-88-2	1 – 10 %			
Ttrimethylhexamethylenediamine	25513-64-8	1 – 10 %			

*Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).

Section	4	First_/	δiλ	Measures
Section	4.	THSL-	₹IU	Measures

Inhalation	IF INHALED: If overexposure remove person to fresh air and keep comfortable for breathing. If symptoms persist, seek
	medical attention.



Ingestion	IF SWALLOWED: Immediately call a doctor. Prevent aspiration of vomit. Never give anything by mouth to an unconscious				
	person. Rinse mouth thoroughly with water.				
Skin contact	IF ON SKIN: Remove contaminated clothing, wash immediately with soap and water (20 - 30 minutes). If skin irritation				
	occurs: Get medical attention. Wash contaminated clothing before reuse. If symptoms persist, seek medical attention.				
Eye contact	IF IN EYES, Rinse cautiously with water for several minutes (20 - 30 minutes). Remove contact lenses, if present and easy to				
	do. Continue rinsing. If eye irritation persists: Get medical attention.				
Most important symptoms and effects (acute or delayed)		Harmful if swallowed, if inhaled. Causes severe skin burns and eye damage.			
		May cause an allergic skin reaction. Suspected of damaging fertility or the			
		unborn child. May cause damage to organs through prolonged or repeated			
		exposure.			
Indication of immediate medical attention/special treatment		In all cases, call a doctor. Do not forget this document.			
Section 5. Fire-Fighting Measures					

Specific hazards of the hazardous product (hazardous combustion products)

Ammonia gas may be liberated at high temperatures. Oxides of carbon and nitrogen.

Suitable and unsuitable extinguishing media

In case of fire: Use Carbon dioxide (CO₂), dry powder, alcohol resistant foam. Limestone powder, dry sand. Do not use water jet as an extinguisher.

Special protective equipment and precautions for fire-fighters

During a fire, gases hazardous to health may be formed. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment as required

Section 6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Evacuate non-emergency personnel. Isolate the area and prevent access. Control source of the leak. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8). Prevent the spill spread into drains, sewers, water supplies, or soil. Removal of ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Avoid prolonged exposure. Stop leak if you can do it without risk. Spill should be contained with inert material and disposed into suitable retaining area. Do not touch or walk through spilled material. Small volumes of liquid may be contained or absorbed into an appropriate absorbent. Keep away from all watercourses. Do not flush down storm or sanitary sewer. Take precautionary measures against static discharges. Dispose of in accordance with local, provincial and federal regulations.

Section 7. Handling and Storage

Precautions for safe handling

Obtain special instruction before use. Do not handle until all safety precautions have been read and understood. Do not/avoid breath dust/ fume/gas/mist/vapours/spry. Wash hands/nails/face/eyes thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear gloves/protective clothing/gloves/eye protection/face protection.

Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated area. Keep container closed when not in use. Do not handle or store near open flames, heat or other sources of ignition. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks. Storage temperature: 16 - 27 °C.

Section 8. Exposure Controls/Personal Protection

Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: ACGIH – TLV-TWA Not available.

Appropriate engineering controls

Use product in well-ventilated areas. Do not spray the product. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Supply emergency safety/quick-drench shower, eyewash station and washing facilities available in work area and near handling area. Where such systems are not effective, wear suitable personal protection equipment which performs satisfactorily and meets recognized standards.

Individual protection measures/personal protective equipment

Gloves: Neoprene gloves or equivalent; Clothing: Shirts with long sleeves, long pants; Respiratory: Not required if working area is well ventilated. Use a NIOSH approved respirators if the exposure limits are unknown; Equipment: Safety glasses, chemical resistant. Special instructions for protection and hygiene: Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use. Educate and train employees in the safe use and handling of this product. Follow all label instructions.

Section 9. Physical and Chemical Properties					
Appearance, physical state/colour Liquid		Vapour pressure	No data available		
Odour	Amine		Vapour density	No data available	
Odour threshold Not available		Relative density	No data available		



pH Alkalines	Solubility No data available		
Melting/freezing point Not available	Partition coefficient - n-octanol/water Not available		
Initial boiling point/range Not available	Auto-ignition temperature Not available		
Flash point > 93,3 °C	Decomposition temperature Not available		
Evaporation rate Not available	Viscosity Not available		
Flammability (solids and gases) Not available	VOC Not available		
Upper and lower flammability/explosive limits Not available	Other None known		

Section 10. Stability and Reactivity

Reactivity

Stable under normal conditions.

Chemical stability

Yes, Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

Non under normal conditions of storage and use.

Conditions to avoid (static discharge, shock or vibration)

Excess heat or contamination.

Incompatible materials

Avoid contact with nitrous acid, oxide, acids and nitrites.

Hazardous decomposition products

Nitric acid, Ammonia Nitrogen Oxides, Carbon Monoxide, Carbon Dioxide. Aldehydes, Nitrosamine.

Section 11. Toxicological Information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

Harmful if swallowed, if inhaled. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Corrosive may cause skin burns.

Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization – May cause allergic skin reaction. May cause skin irritation if contact frequently. Respiratory Sensitization – No data available:

Germ Cell Mutagenicity – Not available; Carcinogenicity – No ingredient listed in IARC; Reproductive Toxicity – Not available;

Specific Target Organ Toxicity — Single Exposure – No information found; Specific Target Organ Toxicity — Repeated Exposure – No information found;

Aspiration Hazard – No information found; Health Hazards Not Otherwise Classified – No data available.

Numerical measures of toxicity (ATE; LD₅₀ & LC₅₀)

CAS 1477-55-0 LD₅₀ Oral - Rabbit > 2000 mg/kg; LD₅₀ Dermal Not available; LC₅₀ Inhalation Not available;

CAS 1761-71-3 LD₅₀ Oral - Rat > 2000 mg/kg; LD₅₀ Dermal Not available; LC₅₀ Inhalation Not available;

ATE not available in this document.

Section 12. Ecological Information

Ecotoxicity (aquatic and terrestrial information)

Fish toxicity CAS 1761-71-3 LC50: > 100 mg/L (Leuciscus idus melanotus, 96h); CAS 25513-64-8 LC50: > 174 mg/L Leuciscus idus melanotus, 48h);

Toxicity to Aquatic Invertebrates: CAS 1761-71-3 EC₅₀: 9.24 mg/l (Daphnia magna 48h); CAS 25513-64-8 EC₅₀: 31.5 mg/l (Daphnia magna) 24h); CAS 135108-88-2 EC₅₀: 15.4 mg/l (Daphnia magna 48h)

Toxicity to Aquatic Plants: CAS 1477-55-0 EC₅₀: 12 mg/l (Desmodesmus subspicatus (green algae) 72h); CAS 1761-71-3 EC₅₀: 141.2 mg/l (Desmodesmus subspicatus 72h); CAS 25513-64-8 EC₅₀: 43.5 mg/l (Pseudokirchneriella subcapitata) 72h); CAS 135108-88-2 EC₅₀: 43.9 mg/l (Alga 72h)

Persistence and degradability No data available.

Bioaccumulative potential No data available.

Mobility in soil No data available

Other adverse effects Very toxic to aquatic life with long lasting effects.

Section 13. Disposal Considerations

Information on safe handling for disposal/methods of disposal/contaminated packaging

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Section 14. Transport Information

UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations

UN 2735; NAME: Amines liquids, corrosives, N.O.S. (Benzene-1,3-dimethaneamine (MXDA), 2,2,4 (OR 2,4,4)-trimethylhexane-1,6-diamine); HAZARD CLASS: 8; PACKING GROUP: II

UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)

UN 2735; NAME: Amines liquids, corrosives, N.O.S. (Benzene-1,3-dimethaneamine (MXDA), 2,2,4 (OR 2,4,4)-trimethylhexane-1,6-diamine); HAZARD CLASS: 8; PACKING GROUP: II.



UN number; Pr	oper shipping name; Class(es); Packing group (PG) of the IATA (air)				
UN 2735; NAME: Amines liquids, corrosives, N.O.S. (Benzene-1,3-dimethaneamine (MXDA), 2,2,4 (OR 2,4,4)-trimethylhexane-1,6-diamine);					
HAZARD CLASS: 8; PACKING GROUP: II.					
Special precautions (transport/conveyance) May also be shipped as a LIMITED QUANTITY in accordance with TDG.					
	Environmental hazards (IMDG or other) Non				
Bulk transport (usually more than 450 L in capacity) Possible					
	Section 15. Regulatory Information				
Safety/health C	anadian regulations specifics This product has been classified in accordance with the hazard criteria of the Hazardous Products				
	Regulations (HPR).				
Environmental Canadian regulations specifics Refer to Section 3 for ingredient(s) of the DSL					
	nvironmental outside regulations specifics				
	SHA information: This product is regulated according to OSHA (29 CFR).				
	sition 65: This product does not contain an ingredient known to the State of California to cause cancer or other reproductive harm				
	A (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.				
United States TC	CSA information: Refer to the ingredients listed in Section 3.				
	Section 16. Other Information				
	st revision of the safety data sheet February 11, 2023 - version 02				
Corrections	Section 2, 3, 11, 12, 15.				
References	Safety Data Sheets from manufacturer/supplier & from Sigma-Aldrich.com & Echa.eurpea.eu				
Abbreviations					
ACGIH	American Conference of Governmental Industrial Hygienists				
ATE	Acute toxicity estimate				
CAS	Chemical Abstract Service				
DSL	Domestic Substance List				
IARC	International Agency for Research on Cancer				
IATA	International Air Transport Association				
IMDG	International Maritime Dangerous Goods Code				
LC	Lethal concentration				
LD	Lethal Dosage				
NIOSH	National Institute for Occupational Safety and Health				
NTP	National Toxicology Program (U.S.A.)				
OSHA	Occupational Safety and Health Administration (U.S.A.)				
PEL	Permissible Exposure Limit				
STEL	Short-term Exposure Limit				
TDG	Transport of dangerous goods in Canada				
TLV	Threshold Limit Value				
TSCA	Toxic Substances Control Act				
TWA	Time Weighted Average				
WHMIS	Workplace Hazardous Materials Information System beurface expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product				

DISCLAMER: Labsurface expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages. Users are responsible to verify whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product.